

DIAMOND LITE™ HOSE

Earl's new Diamond Lite push on hose is an attractive alternative to basic black or blue push on hose. Diamond Lite is lightweight, extremely flexible, non abrasive and is meant for low to medium duty (100 PSI max) applications and has an operating temperature range to 250°F. The SAE-30R7 rubber smooth bore inner core is rated for oil, fuel & emission lines. The exterior is a PET Monofilament that is tightly braided for maximum hose protection. Diamond Lite is amazingly easy to assembly; just cut to length with a pair of heavy duty scissors, add an Earl's Econo-Fit clamp housing, push onto the barb, and tighten the clamp. It comes in three colors: Black braiding with either a Yellow, Blue or Red diamond pattern tracer and three sizes 1/4"ID, 5/16"ID and 3/8"ID. Designed mostly for motorcycle applications, but it can be used in low pressure automotive ones for a more custom look to your engine compartment. A great addition for your Earl's plumbing street & hot rod markets and a sure winner for your motorcycle accounts.



Bulk Part #	Hose ID IN	Hose ID MM	Weight Per Foot	Hose Braid Color
370014ERL	0.25	6.35	0.073	Red
370015ERL	0.3125	7.9375	0.073	Red
370016ERL	0.375	9.525	0.073	Red
370024ERL	0.25	6.35	0.073	Blue
370025ERL	0.3125	7.9375	0.073	Blue
370026ERL	0.375	9.525	0.073	Blue
370034ERL	0.25	6.35	0.073	Yellow
370035ERL	0.3125	7.9375	0.073	Yellow
370036ERL	0.375	9.525	0.073	Yellow

* Sold By the Foot




EZ-FLEX™ HOSE

Earl's new EZ-Flex push on hose has the same inner liner as our new Diamond Lite hose except it is covered in 304 stainless steel braiding. EZ-Flex is lightweight, extremely flexible and is intended for low to medium duty (100 PSI max) applications with an operating temperature range of 250°F. The SAE-30R7 rubber smooth bore inner core is rated for oil, fuel & emission lines. The exterior is tightly braided 304 stainless steel for maximum hose protection. EZ-Flex is easy to assemble; just cut to length with a pair of heavy shears or cut-off saw, add an Earl's Econ-O-Fit™ clamp housing, push onto the barb and tighten the clamp. It is offered in two sizes; 5/16" & 3/8" I.D. Designed mostly for motorcycle applications, but it can be used in low pressure automotive applications for a more custom look to your engine compartment.

Bulk Part #	Hose ID IN	Hose ID MM	Weight Per Foot
370075ERL	0.3125	7.9375	0.073
370076ERL	0.375	9.525	0.073

* Sold By the Foot

www.earlsplumbing.com | Techline: 310-609-1602



NEW PRODUCT INNOVATIONS

#1 IN PERFORMANCE PLUMBING