

# SUPER STOCK™ HOSE

FOR USE WITH SUPER STOCK HOSE ENDS

## HOSE & HOSE ENDS




Earl's SUPER STOCK™ hose is a high quality synthetic rubber hose reinforced by a full coverage interior braided fabric sheath. This superior replacement hose for original equipment applications has found favor with professional racing teams and street performers alike. Available in blue or black SUPER STOCK™ is rated at 250 psi and 250° F. continuous service. To prevent collapse in suction service or for very tight bends, we can supply an internal spiral reinforcing wire. Suitable for fuel, oil and water.

Super Stock™ hose is intended for use with Super Stock™ hose ends only. It is also for use with hose nipples and beaded tubing. No other Earl's hose ends are intended for use with Super Stock™ hose.

Hose Size AN	Hose I.D. (in) (mm)		Hose O.D. (in) (mm)		Max. Op. Pressure (PSI) (Bar)		Min. Bend Radius (in) (mm)		Bulk P/N	6ft./1.8M P/N	10ft./3.0M P/N	20ft./6.1 P/N	33ft./10.1 P/N
Black -4	0.25	6.35	0.47	11.94	250	17.23	2.5	63.5	780004ERL	780604ERL	781004ERL	782004ERL	-
Blue -4	0.25	6.35	0.47	11.94	250	17.23	2.5	63.5	790004ERL	790604ERL	791004ERL	792004ERL	-
Black -6	0.38	9.65	0.63	16.00	250	17.23	3	76.2	780006ERL	780606ERL	781006ERL	782006ERL	783306ERL
Blue -6	0.38	9.65	0.63	16.00	250	17.23	3	76.2	790006ERL	790606ERL	791006ERL	792006ERL	793306ERL
Black -8	0.5	12.70	0.75	19.05	250	17.23	5	127	780008ERL	780608ERL	781008ERL	782008ERL	783308ERL
Blue -8	0.5	12.70	0.75	19.05	250	17.23	5	127	790008ERL	790608ERL	791008ERL	792008ERL	793308ERL
Black -10	0.63	16.00	0.94	23.88	250	17.23	6.0	152.4	780010ERL	780610ERL	781010ERL	782010ERL	-
Blue -10	0.63	16.00	0.94	23.88	250	17.23	6.0	152.4	790010ERL	790610ERL	791010ERL	792010ERL	-
Black -12	0.75	19.05	1	25.40	250	17.23	7	177.8	780012ERL	780612ERL	781012ERL	782012ERL	-
Blue -12	0.75	19.05	1	25.40	250	17.23	7	177.8	790012ERL	790612ERL	791012ERL	792012ERL	-



In recent years various fuel manufacturers have added any number of new unpublished additives to their blends. It is therefore very difficult to know how the tube compound used in the inner liner of our Super-stock, Auto Flex and Perform-O-Flex or any other brand of elastomeric hose will react with a specific fuel. Because of the unknowns described above, we are unable to guarantee that the above listed hoses are the best possible products to use with any specific fuel. If in doubt use teflon lined hose. Super Stock hose is not to be used with brake fluid. On applications where the maximum temperature range is expected, compression of the Super Stock collar is required.



## INNER SUPPORT SPRING

The inner support spring is to be used with Super Stock™ Hose to prevent collapse when in suction service or when very tight bends must be made. It may also be used with other types of hose where it's determined that these conditions may occur.

HOSE NO.	4 FT. LENGTH
10	770410ERL
12	770412ERL

