

EARL'S
ULTRA FLEX 650™
 STAINLESS STEEL BRAIDED HOSE




Temp Rating
 -94°F to +510°F / -70°C to 265°C

Earl's has taken the same inner tubing of our Kevlar hose, and covered it with a high tensile grade 304 stainless steel. You still get all of the same flow rate and flexibility advantages of the Kevlar hose but with additional protection. The carbon lined inner tubing (for static dissipation) is smooth bore with large ID for maximum flow and convoluted exterior support for incredible flexibility. Ultra-Flex stainless is 40% lighter and has an average of 14% larger ID than our premium stainless braided rubber hose. Being Teflon it has a large range of applications: Fuel, Oil, Water, Methanol, and Air as well as a very high vacuum rating – 29Hg. The new stainless hose also accepts all of the same hose ends and crimp collars made for the Kevlar Ultra-Flex line. This means that the same crimper and dies used for the Kevlar hose can be used with the new stainless, so your Ultra-Flex crimper and dies are all you need for all of your high end line assemblies.

Bulk Part #	Hose ID		Hose OD		Working Pres		Min Bend Rad		Weight / FT	
	IN	MM	IN	MM	PSI	BAR	IN	MM	LBS/Ft	GM/Ft
660006ERL	0.394	10.0	0.512	13.0	1180	80	0.787	20	0.110	50
660008ERL	0.536	13.6	0.650	16.5	1030	70	1.496	38	0.132	60
660010ERL	0.658	16.7	0.819	20.8	955	65	1.772	45	0.220	100
660012ERL	0.780	19.8	0.961	24.4	880	60	1.969	50	0.242	110
660016ERL	1.0039	26.4	1.272	32.3	740	50	2.756	70	0.374	170

www.earlspumbing.com | Techline: 310-609-1602



NEW PRODUCT INNOVATIONS

#1 IN PERFORMANCE PLUMBING