


Site Map | Home

HomeProductsServicesCompanyContact

Site Map | Products > Zero Range

Zero Range



Zero 200Zero 300Zero 400

Zero Models

The **Zero Range** is available in three sizes, which are 3.25" (82.5mm), 3.75" (95mm) and 4.75" (120mm) diameter overall, being the **Zero 200**, **Zero 300** and **Zero 400** respectively. The Zero range of filler caps have been designed to take advantage of the latest automotive technology.

Zero 200 - The Zero 200 comes with an integrated 2.00" flange/neck. It is designed to be installed on a remote tank, using a suitable hose. This cap is also offered vented.

Zero 300 - The Zero 300 is designed to be mounted directly on to a tank using the flange.

Zero 400 - The Zero 400 comes with an integrated 2.00" flange/neck. It is designed to be installed on a remote tank, using a suitable hose.

All Zero range models are key operated and are supplied with two keys. There is a limited range of replacement keys available. The key number is not recorded, so a note should be taken of the key number stamped on the key upon installation.

Installation Instructions

A flat and smooth surface should be chosen to successfully install Zero filler caps. Where the filler cap is not in contact with fuel, for example when fitted to the outside skin of a vehicle, it is possible to accommodate a slightly curved surface but care must be taken not to distort the flange by over tightening the fixing screws. With 'wet' installations such as motorcycle and boat tanks, the use of a gasket and sealant is recommended. We recommend 'Hylomar' sealant or a suitable equivalent.