



# Newflex Hoses

**NEWTON**  
EQUIPMENT LTD  
SPECIALIST AUTOMOTIVE COMPONENTS

## Applications

- Engine and automotive industry
- Industrial uses

## Special properties

- High resistance to heat and cold
- Particularly suitable for oils and fuels
- Good abrasion levels and suitable for very damp media
- High resistance to constant vibration



CH 5090

## Construction

- Nitrile rubber wrapped with nylon bandage
- Colour: Black
- Wide range of diameters

## Straights

| Hose      | Inner Diameter | Length | Wall Thickness |
|-----------|----------------|--------|----------------|
| CH 32180  | 32 mm          | 1m     | 1/4 inch       |
| CH38180   | 38 mm          |        |                |
| CH 175180 | 44 mm          |        |                |
| CH 50180  | 50 mm          |        |                |
| CH 57180  | 57 mm          | 1/2 m  |                |
| CH63180   | 63 mm          |        |                |
| CH88180.5 | 88 mm          |        |                |

Owing to the method of construction the wrapped hoses do not bend easily. Straights and elbows should be used as required.

## Elbows

| Hose    | Inner Diameter | Elbow | Length       | Wall       |
|---------|----------------|-------|--------------|------------|
| CH 5045 | 50 mm          | 45°   | 6 - 8 Inches | 1 / 4 Inch |
| CH 5090 | 50 mm          | 90°   |              |            |
| CH 5745 | 57 mm          | 45°   |              |            |
| CH 5790 | 57 mm          | 90°   |              |            |

Newton Equipment Ltd, Ajax Works, Hertford Road, Essex, IG11 8DY, England  
Tel: +44(0) 208 594 7990 Fax: +44(0) 208 594 7989  
E Mail: [info@newton-equipment.com](mailto:info@newton-equipment.com)  
[www.newton-equipment.com](http://www.newton-equipment.com)